TECHNICAL DATA

Version 7

AT4000 Phase Marking Tape

General Description

A PVC film coated with cross – linked solvent based rubber – resin adhesive.
Black printed L1, L2 and L3 in white. Blue printed N in white.

- Flame retardant
- Self-extinguishing
- Flexible
- Excellent conformability to awkward shapes
- · Good abrasion resistance
- · Good resistance to ageing
- UV resistant
- Non-corrosive adhesive



Certification* to the following standards may be available on request. BS EN 60454-3-1/Type 6

Technical Details

Typical Values

Thickness 0.18mm

Breaking Load 40 N/cm

Elongation 250%

Adhesion

Steel 2.3 N/cm Self 1.7 N/cm

Water Extract

0H 7.4

Conductivity Max. 2 mS/m

Electrical Properties

B/down Voltage 10.0 kV 1 MinProof 6.5 kV

Insulation Resis 5 x 10₁₃ ohms

Copper Corrosion No Staining

Flame Retardency Self-extinguishing

RoHS compliant Yes

Service Temperature -5°C to +70°C

Application Temperature 0°C to +40°C

Storage Temperature +12°C to +25°C

*Standard charge for certificate: £25.00.



Except where indicated otherwise, the figures stated are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.





AFERA

Association des Fabricants Européens de Rubans Auto-Adhésifs.

Adding more to adhesive tape

Advance Tapes International Limited

Westmoreland Avenue

Thurmaston Leicester LE4 8PH

England

Tel. +44 (0)116 251 0191 Fax. +44 (0)116 265 2046 contact@advancetapes.com



Q05026